

Butterfly Valve Type 565

				
Type 565 Butterfly Valve with bare shaft	Type 565 Butterfly Valve with hand lever	Type 565 Butterfly Valve with reduction gear	Type 565 Butterfly Valve with pneumatic actuator	Type 565 Butterfly Valve with electric actuator

Product description

The plastic Butterfly Valve Type 565 is the best choice for optimizing piping systems built for water applications and a wide range of other applications. This new generation comes at a significantly lower initial cost, and will save even more thanks to its lower static weight, requiring less energy for both operation and transportation. Installing the Butterfly Valve Type 565 is quick and easy, but thanks to its extremely high durability, it will be almost maintenance-free during its long service life.

Direct replacement: The Butterfly Valve Type 565 comes in the same installation length as metal solutions and can replace them without any additional rework on the pipes.

60 % lighter: Can be lifted installed by a single person in just a few minutes. Facilitates planning and reduces the need for costly transportation and personnel.

Highly reliable: High-performance thermoplastics protect from abrasion and corrosion. A longer system lifetime, reduction of maintenance costs and production stops are the results.

Automated and digitized: Prepared for being actuated by wide range of electric and pneumatic actuators. Future-proof through compatibility with wirelessly controlled Smart Actuators. Prepared mounting option for end position detection sensors.

Sustainable: Long service life as well as corrosion-resistant due to the use of high-quality plastic materials. Significant energy and resource reduction during transport and installation due to low weight.

Information via DataMatrix code: The DataMatrix code simplifies the storage of all technical information for each individual valve and thus enables individual traceability. The perfect identification of each individual Type 565 butterfly valve allows easy installation, maintenance and repair.

Automation through use as a process and control valve

Thanks to a wide range of accessories, butterfly valves can be equipped with the appropriate pneumatic or electric actuators and thus used as process and control valves. Double sensors enable hereby the end position detection (open/closed disc).



Type 565 Butterfly Valve with electric actuator

Type 565 Butterfly Valve with smart actuator

Type 565 Butterfly Valve with pneumatic actuator

Double sensor for end position detection


Applications

Suitable for water and water treatment applications (e.g. sea water, drinking water and industrial water):

- Drinking water process
- Industrial process water
- Industrial waste water
- Municipal waste water
- Desalination plant
- Aquarium/ Oceania
- Swimming pools
- Cruise ships
- Offshore
- Vessels and merchant fleet

Technical data

Specifications



- ① Screw
- ② Lever
- ③ Spring
- ④ Grid lever
- ⑤ Index plate
- ⑥ Washer
- ⑦ Nut
- ⑧ Shaft lock
- ⑨ O-Ring
- ⑩ Shaft
- ⑪ Housing
- ⑫ Cap
- ⑬ Seat liner
- ⑭ Disc

Specifications


Dimensions	d63/DN50 – d315/DN300, 2" – 12"					
Materials	Lever, grid lever, index plate, shaft lock, housing	② ④ ⑤ ⑧ ⑪	Polyamide PA6-60			
	Disc (outside)	⑭	PVDF			
	Disc (inside)	⑭	Polyamide PA6-60			
	O-Ring, seat liner	⑨ ⑬	EPDM or FKM			
	Screw, washer, nut, shaft	① ⑥ ⑦ ⑩	Stainless steel			
	Spring	③	Stainless spring steel			
	Cap	⑫	EPDM			
Pressure ratings	Manual actuated		Electric actuated		Pneumatic actuated	
	DN50-150	PN16	DN50-200	PN10	DN50-250	PN10
	DN200-250	PN10	DN250	PN6	DN300	PN6
	DN300	PN6	DN300	PN4		
Flange standards	ISO 7005 PN10/16, EN 1092 PN10/16, DIN 2501 PN10/16, ANSI/ASME B 16.5 Class 150, BS 1560: 1989 Class 125/150; BS 4504 PN10/16, JIS B 2220 10K, JIS B 2239 10K					
Actuator interface	EN ISO 5211					
Actuation variants	Manually operated (lockable hand lever or manual reduction gear)					
	Pneumatic actuated: FC, FO, DA					
	Electric actuated: EA25-250 AC: 100 – 230 V, AC/DC: 24 V, Smart actuator dEA					
Approvals	Multiple approvals available on request					
	Leak test		ISO 9393-2, EN 12266 (leak rate A), ISO 5208 (Rate A)			

Flow characteristics

Kv 100-values

DN (mm)	d (mm)	Inch (")	Kv 100 (l/min)	Cv 100 (US gal./min)	Kv 100 (m³/h)
50	63	2	1'445	101	87
65	75	2 ½	2'530	177	152
80	90	3	4'020	281	241
100	110	4	5'850	400	351
125	140	5	11'900	832	714
150	160	6	18'050	1'262	1'083
200	225	8	43'667	3'052	2'620
250	280	10	62'333	4'357	3'740
300	315	12	94'500	6'606	5'670

Flow characteristics according to opening angle



Operating torques

DN (mm)	d (mm)	Inch (")	Operating torque @ maximum operating pressure (Nm)
50	63	2	15
65	75	2 ½	20
80	90	3	25
100	110	4	40
125	140	5	50
150	160	6	60
200	225	8	160
250	280	10	250
300	315	12	300

Pressure-temperature diagrams



The following pressure-temperature diagrams are based on a lifetime of 25 years and water or similar media.

T Temperature (°C, °F)

P Permissible pressure (bar, psi)


EPDM (DN50 – DN300)

FKM (DN50 – DN300)



Pressure losses

DN50 – DN250



X Flow rate
(l/min, US gal./min)
Y Pressure loss Δp (bar, psi)

Standard values for screw fastening

DN50 – DN300 in ISO flange connections

DN (mm)	d (mm)	Inch (")	Screws ISO*	Tightening torque	
				(Nm)	(ft lb)
50	63	2	4 x M16 x 140mm	25	18
65	75	2 ½	4 x M16 x 140mm	25	18
80	90	3	8 x M16 x 150mm	25	18
100	110	4	8 x M16 x 160mm	30	22
125	140	5	8 x M16 x 170mm	35	26
150	160	6	8 x M20 x 180mm	40	30
200	225	8	8 x M20 x 200mm	60	44
250	280	10	12 x M20 x 220mm	80	59
300	315	12	12 x M20 x 250mm	80	59

*for PVC-U socket flange adaptors and PP-V flange

DN50 – DN300 in ANSI flange connections

DN (mm)	d (mm)	Inch (")	Screws ANSI*	Tightening torque	
				(Nm)	(ft lb)
50	63	2	4 x 5/8" x 5 ½"	25	18
65	75	2 ½	4 x 5/8" x 5 ½"	25	18
80	90	3	4 x 5/8" x 6"	25	18
100	110	4	8 x 5/8" x 6 ½"	30	22
125	140	5	8 x ¾" x 6 ¾"	35	26
150	160	6	8 x ¾" x 7"	40	30
200	225	8	8 x ¾" x 8"	60	44
250	280	10	12 x 7/8" x 8 ½"	80	59
300	315	12	12 x 7/8" x 10"	80	59


*for PVC-U socket flange adaptors and PP-V flange



Components and tightening torques can be determined using the online tool "Perfect Flange Connection Tool" under the following link:
<https://www.gfps.com/perfectflangeconnection>

Dimensions


Butterfly Valve Type 565 DN50 – DN300 with free shaft end



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Lmax (mm)	Hmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	118.5	85.5	222.5	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	132.5	85.5	248.5	23.0	140.0	82.0	46.0
80	90	3	138.0	138.0	85.5	261.0	23.0	146.0	89.0	46.0
100	110	4	158.5	158.5	85.5	286.0	23.0	166.5	104.0	52.0
125	140	5	187.0	187.0	85.5	313.5	23.0	180.0	118.0	56.0
150	160	6	213.0	213.0	85.5	337.5	23.0	189.0	130.5	56.0
200	225	8	267.0	267.0	85.5	387.0	23.0	209.5	159.0	60.0
250	280	10	325.5	325.5	125.0	498.5	23.0	262.5	195.5	68.0
300	315	12	380.0	380.0	125.0	555.0	23.0	284.5	230.5	78.0

Dimensions			Housing dimensions					Q	Weight
DN (mm)	d (mm)	Inch (")	Acc. to ISO 5211	da1 (mm)	E (mm)	U (mm)	Y (mm)	Q2 (mm)	Weight (kg)
50	63	2	F07	14.1	11.0	90.0	27.0	28.5	1.0
65	75	2 ½	F07	14.1	11.0	90.0	27.0	44.0	1.2
80	90	3	F07	14.1	11.0	90.0	27.0	63.5	1.4
100	110	4	F07	18.1	14.0	90.0	16.0	84.0	2.2
125	140	5	F07	18.1	14.0	90.0	16.0	110.5	2.9
150	160	6	F07	22.2	17.0	90.0	19.0	137.5	3.8
200	225	8	F07	22.2	17.0	90.0	18.0	190.5	5.2
250	280	10	F10	28.2	22.0	125.0	40.5	239.0	9.5
300	315	12	F10	28.2	22.0	125.0	40.5	285.5	13.7


Butterfly Valve Type 565 DN50 – DN200 with hand lever



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	264.0	249.5	96.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	271.0	275.5	96.0	23.0	140.0	82.0	46.0
80	90	3	138.0	273.5	288.0	96.0	23.0	146.0	89.0	46.0
100	110	4	158.5	334.0	324.0	96.0	23.0	166.5	104.0	52.0
125	140	5	187.0	348.0	351.0	96.0	23.0	180.0	118.0	56.0
150	160	6	213.0	426.0	372.5	96.0	23.0	189.0	130.5	56.0
200	225	8	267.0	453.0	422.0	96.0	23.0	209.5	159.0	60.0

Dimensions			Actuator			Q	Weight
DN (mm)	d (mm)	Inch (")	M1 (mm)	M2 (mm)	Y (mm)	Q2 (mm)	Weight (kg)
50	63	2	35.5	204.5	53.0	28.5	1.4
65	75	2 ½	35.5	204.5	53.0	44.0	1.6
80	90	3	35.5	204.5	53.0	63.5	1.8
100	110	4	35.5	254.5	53.0	84.0	2.7
125	140	5	35.5	254.5	53.0	110.5	3.3
150	160	6	35.5	319.5	53.0	137.5	4.3
200	225	8	35.5	319.5	53.0	190.5	5.7


Butterfly Valve Type 565 DN50 – DN300 with manual reduction gear



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	238.5	303.0	169.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	246.0	329.0	169.0	23.0	140.0	82.0	46.0
80	90	3	138.0	248.5	341.5	169.0	23.0	146.0	89.0	46.0
100	110	4	158.5	258.5	377.5	169.0	23.0	166.5	104.0	52.0
125	140	5	187.0	272.0	405.0	169.0	23.0	180.0	118.0	56.0
150	160	6	213.0	285.5	426.5	169.0	23.0	189.0	130.5	56.0
200	225	8	267.0	312.5	475.5	169.0	23.0	209.5	159.0	60.0
250	280	10	325.5	360.5	603.0	212.5	23.0	262.5	195.5	68.0
300	315	12	380.0	387.5	659.5	212.5	23.0	284.5	230.5	78.0

Dimensions			Actuator					Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	LB (mm)	LV (mm)	M (mm)	Y (mm)	Q2 (mm)	Weight (kg)
50	63	2	80.0	128.0	112.5	160.0	61.5	28.5	3.1
65	75	2 ½	80.0	128.0	112.5	160.0	61.5	44.0	3.3
80	90	3	80.0	128.0	112.5	160.0	61.5	63.5	3.5
100	110	4	80.0	128.0	112.5	160.0	61.5	84.0	4.3
125	140	5	80.0	128.0	112.5	160.0	61.5	110.5	5.0
150	160	6	80.0	128.0	112.5	160.0	61.5	137.5	5.8
200	225	8	80.0	128.0	112.5	160.0	61.5	190.5	7.2
250	280	10	100.0	135.5	130.0	200.0	68.5	239.0	13.4
300	315	12	100.0	135.5	130.0	200.0	68.5	285.5	17.6


Butterfly Valve Type 565 DN50 – DN300 with pneumatic actuator PPA and FC/F0



Dimensionen			Gehäuse-Abmessungen								
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H2 (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	121.2	341.2	245.5	20.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	140.0	372.2	343.0	20.0	23.0	140.0	82.0	46.0
80	90	3	138.0	142.4	384.9	343.0	20.0	23.0	146.0	89.0	46.0

Dimensions			Actuator				Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M2 (mm)	Y (mm)	Y1 (mm)	Q2 (mm)	Weight (kg)
50	63	2	119.5	122.8	111.0	15.0	28.5	2.9
65	75	2 ½	141.5	171.5	131.0	0.0	44.0	4.9
80	90	3	141.5	171.5	131.0	0.0	63.5	5.1


Butterfly Valve Type 565 DN50 – DN300 with pneumatic actuator PPA and DA



Dimensionen			Gehäuse-Abmessungen								
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H2 (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	121.2	341.2	183.5	20.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	132.5	367.1	183.5	20.0	23.0	140.0	82.0	46.0
80	90	3	138.0	138.0	379.8	183.5	20.0	23.0	146.0	89.0	46.0

Dimensions			Actuator				Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M2 (mm)	Y (mm)	Y1 (mm)	Q2 (mm)	Weight (kg)
50	63	2	119.5	91.8	111.0	15.0	28.5	2.4
65	75	2 ½	119.5	91.8	111.0	15.0	44.0	2.7
80	90	3	119.5	91.8	111.0	15.0	63.5	2.9


Butterfly Valve Type 565 DN50 – DN300 with pneumatic actuator PA30-90 and FC/F0



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	118.5	309.5	274.5	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	132.5	335.5	275.5	23.0	140.0	82.0	46.0
80	90	3	138.0	138.0	361.0	325.5	23.0	146.0	89.0	46.0
100	110	4	158.5	158.5	385.5	359.5	23.0	166.5	104.0	52.0
125	140	5	187.0	187.0	447.5	418.0	23.0	180.0	118.0	56.0
150	160	6	213.0	213.0	472.5	434.0	23.0	189.0	130.5	56.0
200	225	8	267.0	267.0	545.5	547.5	23.0	209.5	159.0	60.0
250	280	10	325.5	325.5	666.0	681.0	23.0	262.5	195.5	68.0
300	315	12	380.0	380.0	743.0	681.0	23.0	284.5	230.5	78.0

Dimensions			Actuator				Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M2 (mm)	Y (mm)	Y1 (mm)	Q2 (mm)	Weight (kg)
50	63	2	70.5	137.2	98.5	15.0	28.5	3.3
65	75	2 ½	70.5	137.2	98.5	15.0	44.0	3.6
80	90	3	83.5	162.6	111.5	15.0	63.5	4.4
100	110	4	87.0	179.8	115.0		84.0	6.1
125	140	5	107.5	209.0	149.5		110.5	8.2
150	160	6	111.5	217.0	153.5		137.5	11.0
200	225	8	135.0	273.6	177.0		190.5	16.9
250	280	10	148.0	323.0	190.0	18.0	239.0	26.2
300	315	12	168.0	340.5	210.5	18.0	285.5	33.3


Butterfly Valve Type 565 DN50 – DN300 with pneumatic actuator PA30-90 and DA



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	118.5	303.5	196.5	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	132.5	329.5	196.5	23.0	140.0	82.0	46.0
80	90	3	138.0	138.0	348.0	206.0	23.0	146.0	89.0	46.0
100	110	4	158.5	158.5	381.5	242.0	23.0	166.5	104.0	52.0
125	140	5	187.0	187.0	409.0	242.0	23.0	180.0	118.0	56.0
150	160	6	213.0	213.0	468.5	290.5	23.0	189.0	130.5	56.0
200	225	8	267.0	267.0	522.0	314.0	23.0	209.5	159.0	60.0
250	280	10	325.5	325.5	636.0	340.0	23.0	262.5	195.5	68.0
300	315	12	380.0	380.0	709.5	382.5	23.0	284.5	230.5	78.0

Dimensions			Actuator				Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M2 (mm)	Y (mm)	Y1 (mm)	Q2 (mm)	Weight (kg)
50	63	2	64.5	98.5	92.5	15.0	28.5	2.7
65	75	2 ½	64.5	98.5	92.5	15.0	44.0	3.0
80	90	3	70.5	103.0	98.5	15.0	63.5	3.5
100	110	4	83.5	121.0	111.5		84.0	4.7
125	140	5	83.5	121.0	111.5		110.5	5.4
150	160	6	107.5	145.5	149.5		137.5	8.0
200	225	8	111.5	157.0	153.5		190.5	11.2
250	280	10	118.0	170.0	160.0	18.0	239.0	17.6
300	315	12	135.0	191.5	177.0	18.0	285.5	23.6


Butterfly Valve Type 565 DN50 – DN300 with electric actuator EA45-250



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	122.5	377.5	190.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	132.5	411.5	190.0	23.0	140.0	82.0	46.0
80	90	3	138.0	137.5	424.0	190.0	23.0	146.0	89.0	46.0
100	110	4	158.5	158.5	459.5	190.0	23.0	166.5	104.0	52.0
125	140	5	187.0	187.0	487.5	190.0	23.0	180.0	118.0	56.0
150	160	6	213.0	213.0	518.5	190.0	23.0	189.0	130.5	56.0
200	225	8	267.0	267.0	568.0	190.0	23.0	209.5	159.0	60.0
250	280	10	325.5	325.5	674.5	190.0	23.0	262.5	195.5	68.0
300	315	12	380.0	380.0	731.0	190.0	23.0	284.5	230.5	78.0

Dimensions			Actuator				Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M1 (mm)	M2 (mm)	Y (mm)	Q2 (mm)	Weight (kg)
50	63	2	122.5	107.5	83.0	166.5	28.5	3.4
65	75	2 ½	122.5	107.5	83.0	189.5	44.0	4.7
80	90	3	122.5	107.5	83.0	189.5	63.5	4.8
100	110	4	122.5	107.5	83.0	189.5	84.0	5.8
125	140	5	122.5	107.5	83.0	189.5	110.5	6.4
150	160	6	122.5	107.5	83.0	199.5	137.5	9.0
200	225	8	122.5	107.5	83.0	199.5	190.5	10.5
250	280	10	122.5	107.5	83.0	216.5	239.0	15.2
300	315	12	122.5	107.5	83.0	216.5	285.5	19.4


Butterfly Valve Type 565 DN50 – DN200 with electric actuator EA45-250 and manual override



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	385.5	96.0	190.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	385.5	96.0	190.0	23.0	140.0	82.0	46.0
80	90	3	138.0	385.5	96.0	190.0	23.0	146.0	89.0	46.0
100	110	4	158.5	385.5	96.0	190.0	23.0	166.5	104.0	52.0
125	140	5	187.0	385.5	189.5	190.0	23.0	180.0	118.0	56.0
150	160	6	213.0	385.5	106.0	190.0	23.0	189.0	130.5	56.0
200	225	8	267.0	385.5	106.0	190.0	23.0	209.5	159.0	60.0

Dimensions			Actuator						Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M1 (mm)	M2 (mm)	X8 (mm)	Y (mm)	Y2 (mm)	Q2 (mm)	Weight (kg)
50	63	2	122.5	107.5	83.0	297.5	189.5	60.0	28.5	5.6
65	75	2 ½	122.5	107.5	83.0	297.5	189.5	60.0	44.0	5.9
80	90	3	122.5	107.5	83.0	297.5	189.5	60.0	63.5	6.0
100	110	4	122.5	107.5	83.0	297.5	189.5	60.0	84.0	6.8
125	140	5	122.5	107.5	83.0	297.5	189.5	60.0	110.5	7.4
150	160	6	122.5	107.5	83.0	297.5	199.5	60.0	137.5	10.0
200	225	8	122.5	107.5	83.0	297.5	199.5	60.0	190.5	11.5

Butterfly Valve Type 565 DN50 – DN300 with smart electric actuator dEA



Dimensions			Housing dimensions							
DN (mm)	d (mm)	Inch (")	D2 (mm)	Wmax (mm)	Hmax (mm)	Lmax (mm)	H4 (mm)	V (mm)	V1 (mm)	Lg (mm)
50	63	2	100.0	122.5	377.5	190.0	23.0	133.5	63.0	43.0
65	75	2 ½	121.0	132.5	411.5	190.0	23.0	140.0	82.0	46.0
80	90	3	138.0	137.5	424.0	190.0	23.0	146.0	89.0	46.0
100	110	4	158.5	158.5	459.5	190.0	23.0	166.5	104.0	52.0
125	140	5	187.0	187.0	487.5	190.0	23.0	180.0	118.0	56.0
150	160	6	213.0	213.0	518.5	190.0	23.0	189.0	130.5	56.0
200	225	8	267.0	267.0	568.0	190.0	23.0	209.5	159.0	60.0
250	280	10	325.5	325.5	674.5	190.0	23.0	262.5	195.5	68.0
300	315	12	380.0	380.0	731.0	190.0	23.0	284.5	230.5	78.0

Dimensions			Actuator				Q	Weight
DN (mm)	d (mm)	Inch (")	E (mm)	M1 (mm)	M2 (mm)	Y (mm)	Q2 (mm)	Weight (kg)
50	63	2	122.5	107.5	83.0	166.5	28.5	3.4
65	75	2 ½	122.5	107.5	83.0	189.5	44.0	4.7
80	90	3	122.5	107.5	83.0	189.5	63.5	4.8
100	110	4	122.5	107.5	83.0	189.5	84.0	5.8
125	140	5	122.5	107.5	83.0	189.5	110.5	6.4
150	160	6	122.5	107.5	83.0	199.5	137.5	9.0
200	225	8	122.5	107.5	83.0	199.5	190.5	10.5
250	280	10	122.5	107.5	83.0	216.5	239.0	15.2
300	315	12	122.5	107.5	83.0	216.5	285.5	19.4

Accessories


Double Sensor for electrical position feedback

After being mounted in the valve or in the interface module, the double sensor is used to signal the CLOSED or OPEN position of the valve via an electric signal to a controller, supplied by the customer. The switching states are also output optically via two integrated LEDs.

Code	Open Signal color	Closed Signal color	Output circuit	Product picture
198 546 001	LED red	LED green	PNP	
198 546 002	LED green	LED red	PNP	

i Suitable connection cable code 198546150 available as an accessory.


Switching ring for Double Sensor

DN (mm)	Code	Gemäss ISO 5211	SW (mm)	Wmax (mm)	Hmax (mm)	Dimensions	Product picture
50 - 80	199 565 900	F07	11	57.7	12.5		
100 - 125	199 565 901	F07	14	57.7	12.5		
150 - 200	199 565 902	F07	17	57.7	12.5		
250 - 300	199 565 903	F10	22.1	79.8	12.5		

i For manually operated valves an additional switching ring is required. For electrically or pneumatically operated valves, the switching ring is already pre-assembled.

Hand lever

Hand lever incl. fastening screws.

DN (mm)	Code	Wmax (mm)	Lmax (mm)	Gemäss ISO 5211	h1 (mm)	M2 (mm)	Y (mm)	Dimensions	Product picture
50-80	199 565 906	96	251	F07	13.5	204.5	53		
100-125	199 565 907	96	301	F07	13.5	254.5	53		
150-200	199 565 908	96	366	F07	13.5	319.5	53		

Reduction gear

For valve operation via a manual gear with handwheel.

DN (mm)	Code	Product picture
50-200	161 483 471	
250-300	161 483 472	

Gear box with direct mount chain wheel

For valve operation via a manual gear with chainwheel.

- Chains need to be ordered separately.
- A pre-assembly is possible. If needed - please contact your local sales team.

DN (mm)	Code	Product picture
50-80	199 565 984	
100-125	199 565 985	
150-200	199 565 986	
250-300	199 565 987	

Chain to chainwheel

- For 199565980-199565987
- Can be ordered in different lengths. Mass unit is 1 meter.

DN (mm)	Code	Material	Product picture
50-300	199 565 989	Zink plated	
50-300	199 565 990	AISI316	

Electric Actuator EA25-250

The EA45/120/250 electric actuator is mounted on a valve (e.g. ball valve or butterfly valve) and connected to a control system provided by the customer. It actuates the valve with a rotary movement of up to 180°.

DN (mm)	Code	Type	Spannung	Torque max.	Acc. to ISO 5211	Product picture
50	198 153 184	EA45	AC 100-230V	45 Nm	F05* (WS 11/14)	
50	198 153 185	EA45	AC/DC 24V	45 Nm	F05* (WS 11/14)	
50 - 125	198 153 186	EA120	AC 100-230V	120 Nm	F07 (WS17)	
50 - 125	198 153 187	EA120	AC/DC 24V	120 Nm	F07 (WS17)	
150 - 300	198 153 188	EA250	AC 100-230V	250 Nm	F07 (WS17)	
150 - 300	198 153 189	EA250	AC/DC 24V	250 Nm	F07 (WS17)	

Smart Actuator dEA45-250

The Smart Actuator dEA45/120/250 is mounted on a valve (e.g. ball valve or butterfly valve) and connected to a control system provided by the customer. It actuates the valve with a rotary movement up to 180°. The Smart Actuator offers wireless connectivity via NFC and Wi-Fi Direct, as well as control and reading of process data via downloadable App.

DN (mm)	Code	Type	Spannung	Torque max.	Acc. to ISO 5211	Product picture
50	198 153 194	dEA45	AC 100-230V	45 Nm	F05* (WS 11/14)	
50	198 153 195	dEA45	AC/DC 24V	45 Nm	F05* (WS 11/14)	
50 - 125	198 153 196	dEA120	AC 100-230V	120 Nm	F07 (WS17)	
50 - 125	198 153 197	dEA120	AC/DC 24V	120 Nm	F07 (WS17)	
150 - 300	198 153 198	dEA250	AC 100-230V	250 Nm	F07 (WS17)	
150 - 300	198 153 199	dEA250	AC/DC 24V	250 Nm	F07 (WS17)	

Pneumatic Actuator PPA

The PPA pneumatic actuator can be mounted on any rotary valves with an interface according to ISO 5211.

Single-acting FC

DN (mm)	Code	Type	Torque max.	Acc. to ISO 5211	Product picture
50	198 155 401	PPA40	30 Nm	F05	
65 - 80	198 155 801	PPA80	53 Nm	F07	

Single-acting F0

DN (mm)	Code	Type	Torque max.	Acc. to ISO 5211	Product picture
50	198 155 402	PPA40	17 Nm	F05	
65 - 80	198 155 802	PPA80	40 Nm	F07	

Double-acting DA

DN (mm)	Code	Typ	Torque max.	Acc. to ISO 5211	Product picture
50 - 80	198 155 403	PPA40	31 Nm	F05	

Pneumatic Actuator PA30-90

The PA30 - PA90 pneumatic actuator can be mounted on any rotary valves with an interface according to ISO 5211.


Single-acting FC

DN (mm)	Code	Type	Torque max.	Acc. to ISO 5211	Product picture
50 - 65	198 811 617	PA30	30 Nm	F05/07	
80	198 811 601	PA35	53 Nm	F05/07	
100	198 811 609	PA40	60 Nm	F05/07	
125	198 811 603	PA45	90 Nm	F07/10	
150	198 811 610	PA55	180 Nm	F07/10	
200	198 811 652	PA60	240 Nm	F07/10/12	
250	198 811 607	PA65	360 Nm	F10/12	
300	198 811 612	PA70	480 Nm	F10/12	


Single-acting FO

DN (mm)	Code	Typ	Torque max.	Acc. to ISO 5211	Product picture
50 - 65	198 811 627	PA30	30 Nm	F05/07	
80	198 811 628	PA35	53 Nm	F05/07	
100	198 811 629	PA40	60 Nm	F05/07	
125	198 811 630	PA45	90 Nm	F07/10	
150	198 811 631	PA55	180 Nm	F07/10	
200	198 811 653	PA60	240Nm	F07/10/12	
250	198 811 654	PA65	360 Nm	F10/12	
300	198 811 634	PA70	480 Nm	F10/12	

Double-acting DA

DN (mm)	Code	Typ	Torque max.	Acc. to ISO 5211	Product picture
50 - 65	198 811 618	PA35	46 Nm	F03/05	
80	198 811 619	PA40	60 Nm	F05/07	
100 - 125	198 811 604	PA45	106 Nm	F05/07	
150	198 811 606	PA55	180 Nm	F07/10	
200	198 811 614	PA60	240 Nm	F07/10	
250	198 811 608	PA65	360 Nm	F07/10	
300	198 811 615	PA70	480 Nm	F10/12	

Manual override


DN (mm)	Code	Acc. to ISO 5211 (mm)	Lmax (mm)	Wmax (mm)	M9 (mm)	M10 (mm)	X8 (mm)	Y2 (mm)	Dimensions	Product picture
50 - 80	199 565 914	F07	172	250	90	100	298	60		
100 - 125	199 565 915	F07	172	250	90	100	298	60		
150 - 200	199 565 916	F07	172	250	90	100	298	60		

Intermediate elements


Intermediate elements are required as a connection between valve and Actuator. The intermediate elements include different screws, hexagon nuts, washer, switching rings, etc. (depends on actuator and dimension).

Note: The switching ring for the double sensor for electrical position feedback is supplied with each intermediate element.


Intermediate elements for Reduction Gear

DN (mm)	Code	Reduction gear	Acc. to ISO 5211	D5 (mm)	Y1 (mm)	Dimensions	Product picture
50 - 80	199 565 917	161 483 471	F07				
100 - 125	199 565 918	161 483 471	F07				
150 - 200	199 565 919	161 483 471	F07				
250 - 300	199 565 913	161 483 472	F07/F10	125	17		



Intermediate elements for Electric Actuators EA45-250, dEA45-250

DN (mm)	Code	Type	Acc. to ISO 5211	D5 (mm)	Y1 (mm)	Dimensions	Product picture
50	199 565 909	EA45	F05/F07	90	15		
50 - 80	199 565 910	xEA120-250	F07				
100 - 125	199 565 911	xEA120-250	F07				
150 - 200	199 565 912	xEA250	F07				
250 - 300	199 565 913	xEA250	F07/F10	125	17		



Intermediate elements for Pneumatic Actuators PPA, function FC/F0

DN (mm)	Code	Type	Acc. to ISO 5211	D5 (mm)	Y1 (mm)	Dimensions	Product picture
50	199 565 965	PPA40	F05/F07	90	15		
65 - 80	199 565 966	PPA80	F05/F07	-	-		



Intermediate elements for Pneumatic Actuators PPA, function DA

DN (mm)	Code	Type	Acc. to ISO 5211	D5 (mm)	Y1 (mm)	Dimensions	Product picture
50 - 80	199 565 965	PPA40	F05/F07	90	15		

Intermediate elements for Pneumatic Actuators PA30-90, function FC/F0


DN (mm)	Code	Type	Acc. to ISO 5211	D5 (mm)	Y1 (mm)	Dimensions	Product picture
50	199 565 921	PA30	F05/F07	90	15		
65	199 565 921	PA30	F05/F07	90	15		
80	199 565 922	PA35	F05/F07	90	15		
100	199 565 923	PA40	F07				
125	199 565 924	PA45	F07				
150	199 565 925	PA50	F07				
200	199 565 929	PA60	F07/F10	125	18		
250	199 565 927	PA65	F10	125	18		
300	199 565 928	PA70	F10	125	18		

Intermediate elements for Pneumatic Actuators PA30-90, function DA


DN (mm)	Code	Type	Acc. to ISO 5211	D5 (mm)	Y1 (mm)	Dimensions	Product picture
50	199 565 920	PA35	F05/F07	90	15		
65	199 565 920	PA35	F05/F07	90	15		
80	199 565 921	PA40	F05/F07	90	15		
100	199 565 923	PA45	F07				
125	199 565 923	PA45	F07				
150	199 565 925	PA55	F07				
200	199 565 925	PA60	F07	125	18		
250	199 565 926	PA65	F10	125	18		
300	199 565 927	PA70	F10	125	18		

Replacement parts

Replacement seat liner

DN (mm)	EPDM	FKM	Lmax (mm)	Wmax (mm)	Dimensions	Product picture
50	199 565 930	199 565 940	45.2	85.5		
65	199 565 931	199 565 941	48.4	105.5		
80	199 565 932	199 565 942	48.4	122.5		
100	199 565 933	199 565 943	54.6	142.5		
125	199 565 934	199 565 944	59	169.5		
150	199 565 935	199 565 945	59	194.5		
200	199 565 936	199 565 946	63	248		
250	199 565 937	199 565 947	72	304		
300	199 565 938	199 565 948	82.8	358		

Replacement o-ring

DN (mm)	EPDM	FKM	Di	s	Dimensions	Product picture
50-80	199 565 951	199 565 961	13.95	2.62		
100-125	199 565 952	199 565 962	17.13	2.62		
150-200	199 565 953	199 565 963	20.22	3.53		
250-300	199 565 954	199 565 964	24.99	3.53		