



Schedule 40 Clear PVC

- Max Water Pressure at 73°F (22.7°C) with solvent-cemented joints
- Belled-end pipe available upon request
- Must be purchased in full box qty
- 20ft Plain end length available upon request

Size (inch)	Code	Code	PF
¼	H0400025PL1000		
⅜	H0400038PL1000		
½	H0400050PL1000		
¾	H0400075PL1000		
1	H0400100PL1000		
1 ¼	H0400125PL1000		
1 ½	H0400150PL1000		
2	H0400200PL1000		
2 ½	H0400250PL1000		
3	H0400300PL1000		
3 ½	H0400350PL1000		
4	H0400400PL1000		
5	H0400500PL1000		
6	H0400600PL1000		
6 ⅝	H0400613PL1000		
8	H0400800PL1000		
10	H0401000PL1000		
12	H0401200PL1000		

Box Qty (ft)	Average O.D. (inch)	Average I.D. (inch)	min. wall (inch)	Wt/Ft (lbs/ft)	Max Water Pressure (psi)
100	0.540	0.354	0.088	0.081	390
100	0.675	0.483	0.091	0.109	310
350	0.840	0.608	0.109	0.161	300
250	1.050	0.810	0.113	0.214	240
250	1.315	1.033	0.133	0.315	220
200	1.660	1.364	0.140	0.426	180
160	1.900	1.592	0.145	0.509	170
120	2.375	2.049	0.154	0.682	140
80	2.875	2.445	0.203	1.076	150
60	3.500	3.042	0.216	1.409	130
40	4.000	3.520	0.226	1.697	120
40	4.500	3.998	0.237	2.006	110
10	5.563	5.017	0.258	2.726	95
10	6.625	6.031	0.280	3.535	90
10	6.625	6.355	0.130	1.770	45
10	8.625	7.943	0.322	5.305	80
10	10.750	9.976	0.365	7.532	70
10	12.750	11.890	0.406	9.949	70

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.