

PRODUCT SPECIFICATION

PVC SCHEDULE 80 PRESSURE FITTINGS

Solvent Weld

APPLICATION:

Corrosion resistant injection molded PVC pipe fittings, IPS sizes 1/4" through 12" produced to Schedule 80 dimensions, for use at temperatures up to and including 140°F. Pressure rating varies with pipe size and temperature. Generally resistant to most acids, bases, salts, aliphatic solutions, oxidants and halogens. Chemical resistance data must be referenced by the design authority for proper material selection prior to use. Typical applications include chemical processing, plating, chilled water, potable water, water and waste water treatment, chemical drainage, and other industrial applications where corrosive fluids are conveyed.

SCOPE:

This specification establishes minimum manufacturing requirements for Poly (Vinyl Chloride) (PVC) Schedule 80 pressure fittings. These fittings are intended for use in pressure applications where the temperature of the fluid conveyed does not exceed 140°F. These fittings meet or exceed the industry standards set forth by the American Society for Testing and Materials (ASTM) and NSF International ANSI/NSF Standard No. 61 and ANSI/NSF Standard No. 14.

MATERIALS:

The materials used in the manufacture of the fittings shall be a dark gray in color Rigid Poly (Vinyl Chloride) (PVC) Type 1 PVC compound having a Cell Classification of 12454 per ASTM D1784 (also known as Type I, Grade I PVC; PVC 1120.) Materials used in the manufacture of these fittings shall meet the health and safety requirements of ANSI/NSF Standard 61 as being safe for use with potable water.

DIMENSIONS AND PROPERTIES:

All sizes of PVC Schedule 80 injection molded pressure fittings shall be manufactured in strict accordance to the requirements of ASTM D2467 (Schedule 80 socket fittings) or ASTM D2464 (Schedule 80 threaded fittings) as applicable for physical dimensions and tolerances. All schedule 80 PVC injection molded fittings shall consistently meet and/or exceed the Quality Assurance and other requirements of ASTM D2467 or D2464 with regard to material, workmanship, burst pressure, dimensions and product marking. All PVC flanges shall be designed and manufactured to meet ANSI Standard B16.5 CL150 bolt pattern, and carry a maximum internal pressure rating of 150 psi, non-shock at 73°F. All PVC Schedule 80 fittings must also be certified to meet the requirements of ANSI/NSF Standard 61 and ANSI/NSF Standard 14 for use with potable water and shall bear the mark of the Listing agency. These products shall also be certified to NSF/ANSI 372 conforming to the lead content requirements for "lead free" plumbing as defined by the U.S. Safe Drinking Water act and the state laws of California, Vermont, Maryland, and Louisiana.

MARKING:

All sizes of PVC Schedule 80 fittings shall meet the marking requirements of ASTM D2467 or ASTM D2464, which includes as a minimum the manufacturers name and/or trademark, the material designation PVC 1, the NSF mark seal of approval for use with potable water, and the designation D2467 or D2464 as applicable.

Westlake Pipe & Fittings PVC Sch 80 Fittings Conform to the Following Standards and Specifications as applicable:

ASTM D1784 (Material)	Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly (Vinyl Chloride) (CPVC) Compounds. Cell Classification 12454 Type I PVC (formerly known as Type I, Grade I PVC) PVC 1120
ASTM D2466	Standard Specification for Poly (Vinyl Chloride) (PVC) Plastic Pipe Fittings, Schedule 40
ASTM D2467	Socket Type Poly (Vinyl Chloride) (PVC) Plastic Pipe Fittings, Schedule 80
ASTM F1970	Standard Specification for Special Engineered Fittings, Appurtenances or Valves for use in Poly (Vinyl Chloride) or Chlorinated Poly (Vinyl Chloride) (CPVC) Systems
ANSI/ASME B1.20.1	American National Standard Tapered Pipe Threads, General Purpose, Inch
ANSI/ASME B16.5	Pipe Flanges and Flanged Fittings - Westlake Pipe & Fittings Flanges bolt hole dimensions conform to ANSI B16.5 Class 150 bolt pattern.
NSF Standard 61	Drinking Water System Components – Health Effects (Third Party Certification materials are suitable for potable water applications)
NSF Standard 14	Plastics Piping System Components and Related Materials (Third Party Certification products meet applicable ASTM performance requirements and are suitable for potable water applications per NSF Std 61)
USA	Pipe fittings manufactured by Westlake Pipe & Fittings are manufactured in the United States of America

PRODUCT SPECIFICATION

PVC SCHEDULE 80 PRESSURE FITTINGS

Solvent Weld

Nominal Size	* Pipe Maximum W.P. Rating (non-shock) @73°F
1/4"	1130
3/8"	920
1/2"	850
3/4"	690
1"	630
1 1/4"	520
1 1/2"	470
2"	400
2 1/2"	420
3"	370
4"	320
6"	280
8"	250
10"	230
12"	230

* Pressure ratings stated are for pipe. PVC Sch 80 fittings meeting the requirements of ASTM D2467 or D2464 meet the same burst pressure as the same size Sch 80 pipe. There are no working pressure ratings established for fittings per these standards.

** See below for additional information.

Temperature De-Rating

The pipe pressure ratings shown are the maximum allowable working pressure for water, non-shock, at 73°F. Allowable pressure ratings decrease with an increase in temperature. The following temperature de-rating factors must be applied to the working pressure ratings shown to determine the maximum allowable pressure rating at elevated temperatures.

Multiply the working pressure rating shown at 73°F by the appropriate de-rating factor for the elevated temperature selected to determine the maximum allowable pressure rating at that temperature.

PVC Temperature De-Rating Factors

Operating Temp (°F)	De-Rating Factor
73°	1.00
80°	0.88
90°	0.75
100°	0.62
110°	0.51
120°	0.40
130°	0.31
140°	0.22

Example:

What is the maximum allowable pressure rating for 4" PVC SCH 80 pipe operating at a temperature of 110°F?

4" PVC Sch 80 pipe = 320 psi@73°F

4" PVC Sch 80 pipe (320 psi x 0.51) = 163 psi

Maximum allowable pressure rating for 4" PVC Sch 80 pipe non-shock for water operating at a temperature of 110°F = 163 psi



WARNING:
USE OF COMPRESSED AIR OR GAS IN
PVC/CPVC PIPE AND FITTINGS CAN
RESULT IN EXPLOSIVE FAILURES AND
CAUSE SEVERE INJURY OR DEATH.

NOTES:

PVC Schedule 80 Pipe and Fitting Material Equivalents: ASTM D1784 Cell Classification 12454 = PVC Type 1 (formerly Type 1, Grade 1 PVC) = PVC1120 = Rigid PVC = UPVC (Unplasticized PVC).

Solvent Welded joints should be utilized for joining systems operating at or near maximum allowable temperatures for PVC. Westlake Pipe & Fittings does not recommend the use of conventional PVC threaded connections at temperatures above 110°F. Use flanged connections, unions, grooved couplings or other suitable mechanical connections where disassembly is necessary at elevated temperatures. Threading of Schedule 40 pipe is not recommended due to insufficient wall thickness. Thread only Schedule 80 dimensions or heavier walls. Threaded piping systems require a 50% reduction in pressure rating stated for plain-end pipe. Flange components must be installed in accordance with Westlake Pipe & Fittings published Flange Installation Guidelines.


Plastic piping systems must be engineered, installed, operated and maintained in accordance with accepted standards and procedures. Suitability for the intended application should be determined and verified by the designer and/or installer prior to use. Chemical resistance data must be referenced for proper material selection prior to use.

**Although fittings meet the same burst pressure as pipe, working pressure ratings for schedule 80 fittings are not established per ASTM D2464 or D2467. A respected rule of thumb based on practical experience suggests that the working pressure ratings for PVC Sch 40 and Sch 80 molded fittings is 60% of the maximum working pressure rating of the same size and schedule PVC pipe (reference 1987 publication "Operating and Maintaining Piping Systems Using PVC Fittings" by Ron D. Bliesner). Westlake Pipe & Fittings supports this widely accepted rule of thumb. The exception is special engineered fittings such as flanges, unions, and valves that do have working pressure ratings established by the manufacturer (they are typically lower than that of the same size pipe). As is the case with pipe, the maximum allowable working pressure for fittings must be decreased with an increase in temperature using the same material temperature de-rating factors. Factors such as fitting geometry, fitting design, system operating conditions (i.e. actual surge conditions), fluids conveyed, severity of service, temperature and other variables must be considered by the design authority when determining suitability for the intended application. Substantial reductions in working pressure are advisable when handling aggressive chemicals and in high temperature service applications.


SCH 80 - PVC

Pressure Fittings

SCHEDULE 80 PVC




Tee				
Part No	Size (in)	L	H	G
801-002	¼	1 7/8	15/16	5/16
801-003	⅜	2 5/16	1 5/32	13/32
801-005	½	2 25/32	1 3/8	1/2
801-007	¾	3 5/32	1 9/16	9/16
801-010	1	3 25/32	1 7/8	23/32
801-012	1¼	4 9/32	2 5/32	7/8
801-015	1½	4 25/32	2 3/8	1 1/32
801-020	2	5 17/32	2 25/32	1 9/32
801-025	2½	6 17/32	3 1/4	1 1/2
801-030	3	7 7/16	3 3/4	1 27/32
801-040	4	9 1/8	4 19/32	2 11/32
801-060	6	13	6 9/16	3 9/16
801-080	8	18 5/32	9 5/32	4 21/32
801-100	10	22	11 1/32	6
801-120	12	26 1/4	13 5/32	7 5/32



Reducing Tee


Part No	Size (in)	L	H	H1	G	G1
801-101	$\frac{3}{4} \times \frac{3}{4} \times \frac{1}{2}$	3 $\frac{1}{32}$	1 $\frac{1}{2}$	1 $\frac{21}{32}$	$\frac{1}{2}$	$\frac{3}{4}$
801-130	1 x 1 x $\frac{1}{2}$	3 $\frac{9}{32}$	1 $\frac{5}{8}$	1 $\frac{21}{32}$	$\frac{1}{2}$	$\frac{3}{4}$
801-131	1 x 1 x $\frac{3}{4}$	3 $\frac{3}{4}$	1 $\frac{15}{16}$	1 $\frac{3}{4}$	$\frac{13}{16}$	$\frac{3}{4}$
801-168	1 $\frac{1}{4}$ x 1 $\frac{1}{4}$ x 1	4 $\frac{1}{4}$	2 $\frac{1}{8}$	2	$\frac{7}{8}$	$\frac{7}{8}$
801-210	1 $\frac{1}{2}$ x 1 $\frac{1}{2}$ x $\frac{3}{4}$	4 $\frac{3}{4}$	2 $\frac{3}{8}$	2	1	1
801-211	1 $\frac{1}{2}$ x 1 $\frac{1}{2}$ x 1	4 $\frac{3}{4}$	2 $\frac{3}{8}$	2 $\frac{9}{32}$	1 $\frac{1}{16}$	1
801-212	1 $\frac{1}{2}$ x 1 $\frac{1}{2}$ x 1 $\frac{1}{4}$	4 $\frac{3}{4}$	2 $\frac{3}{8}$	2 $\frac{3}{8}$	1	1 $\frac{5}{32}$
801-247	2 x 2 x $\frac{1}{2}$	5 $\frac{17}{32}$	2 $\frac{3}{4}$	2 $\frac{3}{32}$	1 $\frac{9}{32}$	1 $\frac{7}{32}$
801-248	2 x 2 x $\frac{3}{4}$	5 $\frac{17}{32}$	2 $\frac{3}{4}$	2 $\frac{1}{4}$	1 $\frac{1}{4}$	1 $\frac{1}{4}$
801-249	2 x 2 x 1	5 $\frac{17}{32}$	2 $\frac{3}{4}$	2 $\frac{3}{8}$	1 $\frac{1}{4}$	1 $\frac{1}{4}$
801-250	2 x 2 x 1 $\frac{1}{4}$	5 $\frac{3}{32}$	2 $\frac{17}{32}$	2 $\frac{19}{32}$	1	1 $\frac{11}{32}$
801-251	2 x 2 x 1 $\frac{1}{2}$	5 $\frac{1}{8}$	2 $\frac{19}{32}$	2 $\frac{19}{32}$	1 $\frac{1}{16}$	1 $\frac{7}{32}$
801-290	2 $\frac{1}{2}$ x 2 $\frac{1}{2}$ x 1 $\frac{1}{4}$	6 $\frac{17}{32}$	3 $\frac{1}{4}$	3	1 $\frac{1}{2}$	1 $\frac{3}{4}$
801-291	2 $\frac{1}{2}$ x 2 $\frac{1}{2}$ x 1 $\frac{1}{2}$	6 $\frac{17}{32}$	3 $\frac{1}{4}$	2 $\frac{29}{32}$	1 $\frac{1}{2}$	1 $\frac{17}{32}$
801-292	2 $\frac{1}{2}$ x 2 $\frac{1}{2}$ x 2	6 $\frac{1}{2}$	3 $\frac{1}{4}$	3	1 $\frac{1}{2}$	1 $\frac{1}{2}$
801-337	3 x 3 x 1 $\frac{1}{2}$	6 $\frac{1}{2}$	3 $\frac{7}{32}$	3 $\frac{1}{4}$	1 $\frac{5}{16}$	1 $\frac{7}{8}$
801-338	3 x 3 x 2	6 $\frac{7}{16}$	3 $\frac{7}{32}$	3 $\frac{3}{8}$	1 $\frac{5}{16}$	1 $\frac{7}{8}$
801-420	4 x 4 x 2	7 $\frac{7}{32}$	3 $\frac{5}{8}$	3 $\frac{15}{16}$	1 $\frac{11}{32}$	2 $\frac{13}{32}$
801-422	4 x 4 x 3	8 $\frac{5}{16}$	4 $\frac{5}{32}$	4 $\frac{9}{32}$	1 $\frac{29}{32}$	2 $\frac{3}{8}$
801-530	6 x 6 x 3	9 $\frac{3}{4}$	4 $\frac{7}{8}$	5 $\frac{13}{32}$	1 $\frac{7}{8}$	3 $\frac{1}{2}$
801-532	6 x 6 x 4	10 $\frac{3}{4}$	5 $\frac{3}{8}$	5 $\frac{25}{32}$	2 $\frac{3}{8}$	3 $\frac{1}{2}$
801-580	8 x 8 x 3	18 $\frac{5}{32}$	9 $\frac{3}{32}$	10 $\frac{7}{16}$	4 $\frac{19}{32}$	8 $\frac{17}{32}$
801-585*	8 x 8 x 6	18 $\frac{5}{32}$	9 $\frac{3}{32}$	9 $\frac{29}{32}$	4 $\frac{19}{32}$	6 $\frac{29}{32}$
801-623*	10 x 10 x 3	22	11 $\frac{1}{32}$	11 $\frac{15}{16}$	6 $\frac{1}{32}$	10
801-624*	10 x 10 x 4	22	11	11 $\frac{15}{16}$	6 $\frac{1}{32}$	9 $\frac{21}{32}$
801-626*	10 x 10 x 6	22	11	11 $\frac{13}{32}$	6	8 $\frac{7}{16}$
801-628*	10 x 10 x 8	22	11 $\frac{1}{32}$	11 $\frac{15}{32}$	6	7 $\frac{15}{32}$
801-666*	12 x 12 x 6	26 $\frac{1}{4}$	13 $\frac{1}{8}$	14 $\frac{11}{32}$	7 $\frac{5}{32}$	11 $\frac{11}{32}$
801-668*	12 x 12 x 8	26 $\frac{1}{4}$	13 $\frac{1}{8}$	13 $\frac{19}{32}$	7 $\frac{5}{32}$	9 $\frac{9}{16}$
801-670*	12 x 12 x 10	26 $\frac{1}{4}$	13 $\frac{1}{8}$	13 $\frac{5}{8}$	7 $\frac{5}{32}$	8 $\frac{19}{32}$

*Sized with Bushing




Tee


Part No	Size (in)	L	H	H1	G	G1
802-005	$\frac{1}{2}$	2 $\frac{3}{4}$	1 $\frac{13}{32}$	1 $\frac{5}{32}$	$\frac{17}{32}$	$\frac{15}{32}$
802-007	$\frac{3}{4}$	3 $\frac{7}{32}$	1 $\frac{5}{8}$	1 $\frac{1}{4}$	$\frac{5}{8}$	$\frac{9}{16}$
802-010	1	3 $\frac{3}{4}$	1 $\frac{7}{8}$	1 $\frac{7}{8}$	$\frac{3}{4}$	$\frac{11}{16}$
802-012	1 $\frac{1}{4}$	4 $\frac{1}{4}$	2 $\frac{1}{8}$	2 $\frac{5}{32}$	$\frac{7}{8}$	$\frac{7}{8}$
802-015	1 $\frac{1}{2}$	4 $\frac{13}{16}$	2 $\frac{13}{32}$	2 $\frac{3}{32}$	1 $\frac{1}{32}$	1 $\frac{1}{32}$
802-020	2	5 $\frac{19}{32}$	2 $\frac{25}{32}$	2 $\frac{3}{8}$	1 $\frac{9}{32}$	1 $\frac{9}{32}$




Tee						
Part No	Size (in)	L	H	H1	G	G1
802-250	2 x 2 x 1¼	5 1/8	2 9/16	2 1/2	1 1/32	1 19/32
802-251	2 x 2 x 1½	5 1/8	2 9/16	2 1/4	1 1/32	1 5/16
802-291	2½ x 2½ x 1½	6 1/2	3 1/4	2 7/16	1 1/2	1 1/2




Tee				
Part No	Size (in)	L	H	G
805-002	¼	1 11/16	7/8	5/16
805-003	⅜	1 7/8	15/16	13/32
805-005	½	2 5/16	1 5/32	15/32
805-007	¾	2 17/32	1 1/4	9/16
805-010	1	3 3/4	1 7/8	21/32
805-012	1¼	4 11/32	2 5/32	27/32
805-015	1½	4 7/8	2 7/16	15/16
805-020	2	4 17/32	2 1/4	1 5/16
805-025	2½	6 1/32	3 1/32	1 19/32
805-030	3	6 15/32	3 1/4	1 3/4
805-040	4	8 1/8	4 1/16	2 1/2



90° Ell			
Part No	Size (in)	H	G
806-002	¼	15/16	5/16
806-003	⅜	1 1/8	3/8
806-005	½	1 3/8	1/2
806-007	¾	1 9/16	9/16
806-010	1	1 13/16	11/16
806-012	1¼	2 1/8	7/8
806-015	1½	2 7/16	1 1/16
806-020	2	2 3/4	1 1/4
806-025	2½	3 17/32	1 3/4
806-030	3	4 3/32	2 3/16
806-040	4	4 9/16	2 5/16
806-060	6	6 1/2	3 1/2
806-080	8	9 3/32	5 17/32
806-100	10	11 1/16	6 1/32
806-120	12	13 1/8	7 1/8




90° Ell					
Part No	Size (in)	H	H1	G	G1
807-005	½	1 3/8	1 1/3	1/2	1/2
807-007	¾	1 3/4	1 3/4	3/4	3/4
807-010	1	1 7/8	1 8/9	3/4	3/4
807-012	1¼	2 3/16	2 3/16	3/4	3/4
807-015	1½	2 3/8	1 29/32	1	1
807-020	2	2 3/4	2 1/4	1 1/4	1 1/4



90° EII


Part No	Size (in)	H	G	T
808-002	¼	27/32	5/16	9/16
808-003	⅜	15/16	13/32	17/32
808-005	½	1 3/8	1/2	7/8
808-007	¾	1 3/4	3/4	1
808-010	1	1 5/8	23/32	7/8
808-012	1¼	2 3/16	25/32	1 3/8
808-015	1½	1 29/32	1	15/16
808-020	2	2 1/4	1 9/32	1
808-025	2½	2 13/16	1 15/32	1 11/32
808-030	3	2 7/32	1 25/32	1 7/16
808-040	4	4	2 1/4	1 3/4



11¼° EII


Part No	Size (in)	H1	H2	J
861-100*	10*	6 5/8	6 5/8	1
861-120*	12	7 9/32	7 7/16	1

H1 & H2 is lay length of each side



22 ½° EII


Part No	Size (in)	H	J
865-020	2	1 15/16	7/16
865-030	3	2 7/16	9/16



22 ½° EII


Part No	Size (in)	H1	H2	J
865-100*	10	6 15/16	7 1/16	1 1/2
865-120*	12	7 31/32	8 3/8	1 3/4

H1 & H2 is lay length of each side




30° EII


Part No	Size (in)	H	J
815-060	6	4	1




45° Ell			
Part No	Size (in)	H	J
817-002	¼	13/16	1/8
817-003	⅜	15/16	3/16
817-005	½	1 1/8	1/4
817-007	¾	1 5/16	5/16
817-010	1	1 1/2	3/8
817-012	1¼	1 23/32	7/16
817-015	1½	1 7/8	1/2
817-020	2	2 1/8	5/8
817-025	2½	2 1/2	3/4
817-030	3	2 25/32	7/8
817-040	4	3 5/16	1
817-060	6	4 3/4	1 3/4
817-080	8	6 13/16	2 5/16
817-100	10	7 7/16	2 7/16
817-120	12	9	2 15/16



45° Ell				
Part No	Size (in)	H	J	T
819-005	½	1 1/32	1/4	3/4
819-007	¾	1 3/16	3/8	13/16
819-010	1	1 11/32	3/8	1
819-012	1¼	1 13/32	3/8	1 1/32
819-015	1½	1 1/2	1/2	1 1/32
819-020	2	1 3/4	11/16	1 1/16
819-025	2½	2 17/32	31/32	1 3/8
819-030	3	2 7/16	3/4	1 11/16
819-040	4	2 25/32	1	1 25/32




Cross				
Part No	Size (in)	L	H	G
820-015	1½	4 3/4	2 3/8	1
820-020	2	6 1/8	3 1/16	1 1/4
820-030	3	8 1/4	4 1/8	1 13/16
820-040	4	9 3/4	4 7/8	2 5/8



Coupling


Part No	Size (in)	L	N
829-002	¼	1 11/32	1/16
829-003	⅜	1 5/8	1/8
829-005	½	1 7/8	1/8
829-007	¾	2 1/8	1/8
829-010	1	2 1/2	1/4
829-012	1¼	2 13/16	1/4
829-015	1½	3 1/16	1/4
829-020	2	3 5/16	1/4
829-025	2½	3 25/32	1/4
829-030	3	4	1/4
829-040	4	4 3/4	3/16
829-060	6	6 5/16	1/4
829-080	8	9 5/16	1/4
829-100	10	10 3/8	5/16
829-120	12	12 7/16	3/8



Reducer Coupling

Part No	Size (in)	L	N
829-101	¾ x ½	2 5/32	1/8
829-131	1 x ¾	2 1/4	1/8
829-168	1¼ x 1	2 17/32	1/8
829-210	1½ x ¾	2 7/8	17/32
829-211	1½ x 1	2 21/32	1/8
829-212	1½ x 1¼	2 13/16	1/8
829-251	2 x 1½	3 1/16	1/8
829-338	3 x 2	3 5/8	3/16
829-422	4 x 3	4 3/8	1/4
829-532*	6 x 4	6 13/16	1 1/2
829-585	8 x 6	10 25/32	2 23/32
829-619*	10 x 2	11 9/32	4 3/4
829-623*	10 x 3	11 9/32	4 3/8
829-624*	10 x 4	11 9/32	4
829-626*	10 x 6	10 25/32	2 3/8


*Sized with Bushing



Coupling

Part No	Size (in)	L	N	Body Dia.
830-002	¼	1 5/16	1/4	27/32
830-005	½	2	1/4	1 5/16
830-007	¾	2 1/4	1/4	1 9/16
830-010	1	2 1/2	1/4	1 27/32
830-012	1¼	2 25/32	1/4	2 7/32
830-015	1½	3 1/16	1/4	2 1/2
830-020	2	3 5/16	1/4	3
830-025	2½	3 3/8	1/4	3 3/4
830-030	3	3 9/16	5/16	4 7/32
830-040	4	3 3/4	7/16	5 1/2


Body diameter measured across hex flats (if applicable)



Female Adapter

Part No	Size (in)	L	N	Body Dia.
835-002	¼	1 7/16	3/16	15/16
835-005	½	2	1/4	1 3/8
835-007	¾	2 1/4	1/4	1 9/16
835-010	1	2 1/2	1/4	1 7/8
835-012	1¼	2 25/32	1/4	2 7/32
835-015	1½	3 1/16	1/4	2 17/32
835-020	2	3 5/16	1/4	3 1/16
835-025	2½	3 13/16	1/4	3 5/8
835-030	3	4 1/16	1/4	4 11/32
835-040	4	4 25/32	1/4	5 1/2


Body diameter measured across hex flats (if applicable)



Male Adapter

Part No	Size (in)	L	N	H	Q
836-005	½	1 7/8	1/4	1	1 7/32
836-007	¾	2	1/4	1 1/32	1 7/16
836-010	1	2 3/8	1/4	1 7/32	1 3/4
836-012	1¼	2 9/16	1/4	1 9/32	2 1/8
836-015	1½	2 11/16	5/16	1 5/16	2 3/8
836-020	2	2 29/32	5/16	1 3/8	2 7/8
836-025	2½	3 11/16	3/8	1 31/32	3 1/2
836-030	3	3 15/16	3/8	2	4 5/32
836-040	4	4 1/2	15/32	2 7/32	5 9/32


Q is Hex outside diameter measured across flats



Reducer Bushing (Flush Style)				
Part No	Size (in)	L	N	Hex O.D.
837-052	$\frac{3}{8} \times \frac{1}{4}$	1	$\frac{3}{8}$	$\frac{3}{4}$
837-072	$\frac{1}{2} \times \frac{1}{4}$	$1 \frac{3}{16}$	$\frac{9}{16}$	$\frac{7}{8}$
837-073	$\frac{1}{2} \times \frac{3}{8}$	$1 \frac{7}{32}$	$\frac{7}{16}$	$\frac{7}{8}$
837-101	$\frac{3}{4} \times \frac{1}{2}$	$1 \frac{1}{16}$	$\frac{1}{4}$	$1 \frac{3}{32}$
837-130	$1 \times \frac{1}{2}$	$1 \frac{7}{16}$	$\frac{17}{32}$	$1 \frac{3}{8}$
837-131	$1 \times \frac{3}{4}$	$1 \frac{1}{4}$	$\frac{15}{32}$	$1 \frac{3}{8}$
837-166	$1\frac{1}{4} \times \frac{1}{2}$	$1 \frac{9}{16}$	$\frac{11}{16}$	$1 \frac{27}{32}$
837-167	$1\frac{1}{4} \times \frac{3}{4}$	$1 \frac{9}{16}$	$\frac{1}{2}$	$1 \frac{25}{32}$
837-168	$1\frac{1}{4} \times 1$	$1 \frac{9}{16}$	$\frac{7}{16}$	$1 \frac{27}{32}$
837-209	$1\frac{1}{2} \times \frac{1}{2}$	$1 \frac{11}{16}$	$\frac{13}{16}$	$2 \frac{1}{16}$
837-210	$1\frac{1}{2} \times \frac{3}{4}$	$1 \frac{11}{16}$	$\frac{5}{8}$	$2 \frac{1}{16}$
837-211	$1\frac{1}{2} \times 1$	$1 \frac{11}{16}$	$\frac{9}{16}$	$2 \frac{1}{32}$
837-212	$1\frac{1}{2} \times 1\frac{1}{4}$	$1 \frac{11}{16}$	$\frac{15}{32}$	$2 \frac{1}{16}$
837-247	$2 \times \frac{1}{2}$	$1 \frac{13}{16}$	$\frac{15}{16}$	$2 \frac{1}{2}$
837-248	$2 \times \frac{3}{4}$	$1 \frac{13}{16}$	$\frac{25}{32}$	$2 \frac{1}{2}$
837-249	2×1	$1 \frac{13}{16}$	$\frac{25}{32}$	$2 \frac{1}{2}$
837-250	$2 \times 1\frac{1}{4}$	$1 \frac{13}{16}$	$\frac{9}{16}$	$2 \frac{1}{2}$
837-251	$2 \times 1\frac{1}{2}$	$1 \frac{13}{16}$	$\frac{3}{8}$	$2 \frac{7}{16}$
837-289	$2\frac{1}{2} \times 1$	$2 \frac{5}{16}$	$1 \frac{1}{4}$	$2 \frac{15}{16}$
837-290	$2\frac{1}{2} \times 1\frac{1}{4}$	2.31	1.07	3
837-291	$2\frac{1}{2} \times 1\frac{1}{2}$	$2 \frac{5}{16}$	$\frac{29}{32}$	$2 \frac{15}{16}$
837-292	$2\frac{1}{2} \times 2$	$2 \frac{7}{32}$	$\frac{11}{16}$	$2 \frac{15}{16}$
837-335	3×1	$2 \frac{15}{32}$	$1 \frac{5}{16}$	$3 \frac{9}{16}$
837-336	$3 \times 1\frac{1}{4}$	$2 \frac{7}{16}$	$1 \frac{3}{16}$	$3 \frac{9}{16}$
837-337	$3 \times 1\frac{1}{2}$	$2 \frac{15}{32}$	$1 \frac{3}{32}$	$3 \frac{9}{16}$
837-338	3×2	$2 \frac{1}{4}$	$\frac{3}{4}$	$3 \frac{17}{32}$
837-339	$3 \times 2\frac{1}{2}$	$2 \frac{15}{32}$	$\frac{11}{16}$	$3 \frac{5}{8}$
837-420	4×2	$2 \frac{13}{16}$	$1 \frac{9}{32}$	$4 \frac{9}{16}$
837-421*	$4 \times 2\frac{1}{2}$	$3 \frac{7}{32}$	$1 \frac{7}{16}$	$3 \frac{5}{8}$
837-422	4×3	$2 \frac{21}{32}$	$\frac{23}{32}$	$4 \frac{9}{16}$
837-528	6×2	$3 \frac{17}{32}$	2	$6 \frac{15}{16}$
837-530	6×3	$3 \frac{17}{32}$	$1 \frac{21}{32}$	$6 \frac{15}{16}$
837-532	6×4	$3 \frac{17}{32}$	$1 \frac{3}{4}$	$6 \frac{15}{16}$
837-585	8×6	$5 \frac{5}{16}$	$2 \frac{5}{16}$	$8 \frac{3}{4}$
837-624*	10×4	$5 \frac{31}{32}$	$3 \frac{11}{16}$	$6 \frac{31}{32}$
837-626	10×6	$5 \frac{7}{16}$	$2 \frac{7}{16}$	$11 \frac{9}{16}$
837-628	10×8	$5 \frac{7}{16}$	$1 \frac{7}{16}$	$11 \frac{9}{16}$
837-666*	12×6	$6 \frac{7}{8}$	$2 \frac{7}{8}$	$11 \frac{19}{32}$
837-668	12×8	$6 \frac{13}{32}$	$2 \frac{3}{8}$	$13 \frac{3}{4}$
837-670	12×10	$6 \frac{15}{32}$	$1 \frac{7}{16}$	$13 \frac{3}{4}$

*Sized with Bushing


Hex outside diameter measured across hex flats



Reducer Bushing (Flush Style)


Part No	Size (in)	L	N	SPG	Hex O.D.
838-052	$\frac{3}{8} \times \frac{1}{4}$	1	$\frac{3}{8}$	$\frac{25}{32}$	$\frac{13}{16}$
838-072	$\frac{1}{2} \times \frac{1}{4}$	$1 \frac{3}{16}$	$\frac{15}{32}$	$\frac{7}{8}$	$\frac{7}{8}$
838-098	$\frac{3}{4} \times \frac{1}{4}$	$1 \frac{7}{32}$	$\frac{5}{8}$	1	$1 \frac{3}{16}$
838-101	$\frac{3}{4} \times \frac{1}{2}$	$1 \frac{1}{16}$	$\frac{1}{4}$	$\frac{25}{32}$	$1 \frac{1}{16}$
838-130	$1 \times \frac{1}{2}$	$1 \frac{1}{4}$	$\frac{1}{2}$	1	$1 \frac{3}{8}$
838-131	$1 \times \frac{3}{4}$	$1 \frac{1}{4}$	$\frac{13}{32}$	1	$1 \frac{11}{32}$
838-166	$1\frac{1}{4} \times \frac{1}{2}$	$1 \frac{9}{16}$	$\frac{1}{2}$	$1 \frac{1}{4}$	$1 \frac{25}{32}$
838-167	$1\frac{1}{4} \times \frac{3}{4}$	$1 \frac{9}{16}$	$\frac{3}{4}$	$1 \frac{1}{4}$	$1 \frac{13}{16}$
838-168	$1\frac{1}{4} \times 1$	$1 \frac{9}{16}$	$\frac{19}{32}$	$1 \frac{1}{4}$	$1 \frac{13}{16}$
838-209	$1\frac{1}{2} \times \frac{1}{2}$	$1 \frac{5}{8}$	$\frac{7}{8}$	$1 \frac{5}{16}$	2
838-210	$1\frac{1}{2} \times \frac{3}{4}$	$1 \frac{5}{8}$	$\frac{3}{4}$	$1 \frac{5}{16}$	2
838-211	$1\frac{1}{2} \times 1$	$1 \frac{11}{16}$	$\frac{13}{16}$	$\frac{11}{16}$	$2 \frac{1}{16}$
838-212	$1\frac{1}{2} \times 1\frac{1}{4}$	$1 \frac{11}{16}$	$\frac{5}{16}$	$1 \frac{3}{8}$	$2 \frac{1}{16}$
838-247	$2 \times \frac{1}{2}$	$1 \frac{11}{16}$	$\frac{13}{16}$	$1 \frac{3}{8}$	$2 \frac{1}{2}$
838-248	$2 \times \frac{3}{4}$	$1 \frac{11}{16}$	$\frac{15}{16}$	$1 \frac{3}{8}$	$2 \frac{1}{2}$
838-249	2×1	$1 \frac{11}{16}$	$\frac{5}{8}$	$1 \frac{3}{8}$	$2 \frac{1}{2}$
838-250	$2 \times 1\frac{1}{4}$	$1 \frac{13}{16}$	$\frac{15}{16}$	$1 \frac{1}{2}$	$2 \frac{9}{16}$
838-251	$2 \times 1\frac{1}{2}$	$1 \frac{13}{16}$	$\frac{3}{8}$	$1 \frac{1}{2}$	$2 \frac{9}{16}$
838-292	$2\frac{1}{2} \times 2$	$2 \frac{5}{16}$	$\frac{3}{4}$	2	$3 \frac{1}{8}$
838-338	3×2	$2 \frac{5}{16}$	$1 \frac{11}{32}$	$1 \frac{29}{32}$	$3 \frac{17}{32}$
838-339	$3 \times 2\frac{1}{2}$	$2 \frac{3}{8}$	$\frac{13}{16}$	2	$3 \frac{5}{8}$
838-420	4×2	$2 \frac{7}{16}$	$1 \frac{1}{2}$	2	$4 \frac{1}{2}$
838-422	4×3	$2 \frac{21}{32}$	$\frac{7}{8}$	$2 \frac{1}{4}$	$4 \frac{9}{16}$
838-532	6×4	$3 \frac{15}{32}$	$2 \frac{1}{8}$	$2 \frac{31}{32}$	$6 \frac{3}{4}$

Hex outside diameter measured across hex flats




Reducer Bushing (Flush Style)

Part No	Size (in)	L	N	T1
839-052	$\frac{3}{8} \times \frac{1}{4}$	$\frac{7}{8}$	$\frac{1}{4}$	$\frac{21}{32}$
839-072	$\frac{1}{2} \times \frac{1}{4}$	$1 \frac{1}{8}$	$\frac{1}{2}$	$\frac{3}{4}$
839-073	$\frac{1}{2} \times \frac{3}{8}$	$1 \frac{1}{8}$	$\frac{1}{2}$	$\frac{25}{32}$
839-098	$\frac{3}{4} \times \frac{1}{4}$	$1 \frac{1}{8}$	$\frac{1}{2}$	$\frac{25}{32}$
839-099	$\frac{3}{4} \times \frac{3}{8}$	$1 \frac{1}{8}$	$\frac{1}{2}$	$\frac{25}{32}$
839-101	$\frac{3}{4} \times \frac{1}{2}$	1	$\frac{5}{16}$	$\frac{11}{16}$
839-128	$1 \times \frac{1}{4}$	$1 \frac{1}{8}$	$\frac{9}{16}$	$\frac{25}{32}$
839-129	$1 \times \frac{3}{8}$	$1 \frac{7}{16}$	$\frac{3}{4}$	$\frac{31}{32}$
839-130	$1 \times \frac{1}{2}$	$1 \frac{7}{16}$	0.62	$\frac{15}{16}$
839-131	$1 \times \frac{3}{4}$	$1 \frac{1}{8}$	$\frac{3}{8}$	$\frac{3}{4}$
839-166	$1 \frac{1}{4} \times \frac{1}{2}$	$1 \frac{11}{32}$	0.55	$\frac{7}{8}$
839-167	$1 \frac{1}{4} \times \frac{3}{4}$	$1 \frac{5}{16}$	$\frac{17}{32}$	$\frac{7}{8}$
839-168	$1 \frac{1}{4} \times 1$	$1 \frac{5}{16}$	$\frac{5}{16}$	$\frac{7}{8}$
839-209	$1 \frac{1}{2} \times \frac{1}{2}$	$\frac{13}{32}$	$\frac{5}{8}$	$\frac{31}{32}$
839-210	$1 \frac{1}{2} \times \frac{3}{4}$	$1 \frac{7}{16}$	$\frac{5}{8}$	1
839-211	$1 \frac{1}{2} \times 1$	$1 \frac{7}{16}$	$\frac{1}{4}$	1
839-212	$1 \frac{1}{2} \times 1 \frac{1}{4}$	$1 \frac{7}{16}$	$\frac{13}{32}$	1
839-247	$2 \times \frac{1}{2}$	$\frac{13}{32}$	$\frac{5}{8}$	1
839-248	$2 \times \frac{3}{4}$	$1 \frac{7}{16}$	$\frac{5}{8}$	$1 \frac{1}{16}$
839-249	2×1	$1 \frac{7}{16}$	$\frac{15}{32}$	$1 \frac{1}{16}$
839-250	$2 \times 1 \frac{1}{4}$	$1 \frac{7}{16}$	$\frac{15}{32}$	$1 \frac{1}{16}$
839-251	$2 \times 1 \frac{1}{2}$	$1 \frac{1}{2}$	$\frac{15}{32}$	$1 \frac{3}{32}$
839-292	$2 \frac{1}{2} \times 2$	$1 \frac{13}{16}$	$\frac{3}{4}$	$1 \frac{9}{16}$
839-337	$3 \times 1 \frac{1}{2}$	$2 \frac{1}{16}$	$\frac{31}{32}$	$1 \frac{5}{8}$
839-338	3×2	$2 \frac{1}{32}$	1	$1 \frac{5}{8}$
839-339	$3 \times 2 \frac{1}{2}$	$2 \frac{1}{16}$	$\frac{1}{2}$	$1 \frac{5}{8}$
839-420	4×2	$2 \frac{1}{16}$	1	$1 \frac{11}{16}$
839-422	4×3	$2 \frac{1}{8}$	$\frac{1}{2}$	$1 \frac{3}{4}$




Reducer Bushing (Flush Style)


Part No	Size (in)	L	N	T1
845-249	2×1	$1 \frac{1}{2}$	$\frac{15}{32}$	$1 \frac{1}{16}$




Cap			
Part No	Size (in)	L	S
847-002	¼	31/32	5/8
847-003	⅜	1	3/4
847-005	½	1 7/32	15/16
847-007	¾	1 3/8	1
847-010	1	1 5/8	1 1/8
847-012	1¼	1 13/16	1 9/32
847-015	1½	2	1 13/32
847-020	2	2 3/32	1 1/2
847-025	2½	2 11/16	1 7/8
847-030	3	2 31/32	1 31/32
847-040	4	3 1/8	2 1/2
847-060	6	4 15/16	3 1/16
847-080	8	6 9/16	4 3/8
847-100	10	8 1/2	5 1/32
847-120	12	10 7/32	6



Cap			
Part No	Size (in)	L	T
848-002	¼	15/16	5/8
848-003	⅜	31/32	17/32
848-005	½	1 3/16	13/16
848-007	¾	1 3/8	1
848-010	1	1 19/32	1 3/16
848-012	1¼	1 3/4	2 7/32
848-015	1½	2	1 3/8
848-020	2	2 1/16	1 1/2
848-025	2½	2 11/16	1 13/16
848-030	3	2 31/32	1 15/16
848-040	4	2 1/2	1 11/16




Plug			
Part No	Size (in)	L	S
849-007	¾	1 9/32	1 1/32
849-010	1	1 13/32	1 1/8
849-012	1¼	1 5/8	1 9/32
849-015	1½	1 11/16	1 3/8
849-020	2	1 29/32	1 1/2



Plug


Part No	Size (in)	L	T
850-002	¼	7/8	5/8
850-003	⅜	29/32	5/8
850-005	½	1	3/4
850-007	¾	1 1/16	25/32
850-010	1	1 1/4	1
850-012	1¼	1 9/32	27/32
850-015	1½	1 3/16	7/8
850-020	2	2	1 5/8
850-025	2½	2 1/16	1 21/32
850-030	3	2 1/8	1 3/4
850-040*	4	2 5/32	1 3/4

*Overall Length includes protruding feature on top of part




Flange (Solid Style)

Part No	Size (in)	D	L	N	R	Bolt Circle Dia.
851-005	½	3 1/2	1	1/8	15/32	2 11/32
851-007	¾	3 29/32	1 5/32	1/8	1/2	2 3/4
851-010	1	4 9/32	1 9/32	3/16	19/32	3 3/32
851-012	1¼	4 21/32	1 13/32	3/16	5/8	3 7/16
851-015	1½	5	1 17/32	1/8	11/16	3 27/32
851-020	2	6 1/32	1 11/16	3/16	25/32	4 3/4
851-025	2½	7	2 3/32	5/16	15/16	5 1/2
851-030	3	7 1/2	2 1/8	1/4	1	6
851-040	4	9	2 1/2	1/4	1	7 7/16
851-060	6	10 31/32	3 7/16	7/16	1 5/16	9 1/2




Flange (Solid Style)

Part No	Size (in)	D	L	N	R	Bolt Circle Dia.
852-005	½	3 1/2	15/16	3/16	7/16	2 11/32
852-007	¾	3 7/8	1 1/8	5/16	1/2	2 3/4
852-010	1	4 1/4	1 3/16	3/16	9/16	3 1/8
852-012	1¼	4 5/8	1 3/8	1/4	5/8	3 15/32
852-015	1½	5	1 1/2	13/32	23/32	3 7/8
852-020	2	6 3/32	1 11/16	19/32	25/32	4 23/32
852-025	2½	7	1 7/8	3/16	7/8	5 15/32
852-030	3	7 1/2	1 7/8	13/32	1	6
852-040	4	9 3/32	2 3/8	9/16	15/16	7 7/16



Flange


Part No	Size (in)	D	L	R	Bolt Circle Dia.
853-005	½	3 1/2	1/2	7/16	2 3/8
853-007	¾	3 7/8	1/2	7/16	2 3/4
853-010	1	4 1/4	19/32	19/32	3 1/8
853-012	1¼	4 5/8	5/8	9/16	3 1/2
853-015	1½	5	13/16	23/32	3 7/8
853-020	2	6	15/16	3/4	4 3/4
853-025	2½	7	1	29/32	5 7/16
853-030	3	7 1/2	1	7/8	6
853-040	4	9	1 3/8	1 1/8	7 1/2
853-060	6	11	1 1/2	1 3/4	9 1/2
853-080	8	13 1/2	1 5/8	1 7/16	11 3/4



Flange (Loose Ring)

Part No	Size (in)	D	L	N	R	Bolt Circle Dia.
854-005	½	3 1/2	1	1/8	19/32	2 3/8
854-007	¾	3 7/8	1 5/32	1/8	19/32	2 3/4
854-010	1	4 1/4	1 3/8	1/8	21/32	3 1/8
854-012	1¼	4 5/8	1 1/2	1/8	11/16	3 1/2
854-015	1½	5	1 11/16	1/4	3/4	3 7/8
854-020	2	6	1 3/4	3/16	13/16	4 3/4
854-030FT	3	7 19/32	2 1/8	3/16	1	6
854-040FT	4	9 1/16	2 1/2	1/4	1 7/32	7 7/16
854-050FT	5	10	2 7/8	1/4	1 1/4	8 1/2
854-060FT	6	10 15/16	3 9/32	1/4	1 5/16	9 1/2
854-080FT	8	13 9/16	4 1/2	1/4	1 1/2	11 3/4
854-100FT	10	16	6	7/16	1 9/16	14 3/8
854-120FT	12	19 1/32	7 17/32	9/16	1 11/16	17


FT Represents FiberTuff Ring.



Flange (Loose Ring)


Part No	Size (in)	D	L	N	R	Bolt Circle Dia.
856-005	½	3 1/2	1 3/4	7/8	17/32	2 3/8
856-007	¾	3 7/8	1 7/8	13/16	19/32	2 3/4
856-010	1	4 1/4	2 1/8	15/16	21/32	3 1/8
856-012	1¼	4 5/8	2 9/32	31/32	11/16	3 1/2
856-015	1½	5	2 1/2	1 1/16	3/4	3 7/8
856-020	2	6	2 13/16	1 7/32	13/16	4 3/4
856-030FT	3	7 19/32	3 11/32	1 5/16	1	5 15/16
856-040FT	4	9	3 7/8	1 5/8	1 7/32	7 7/16
856-050FT	5	10	4 1/2	1 1/2	1 1/4	8 1/2
856-060FT	6	10 15/16	4 11/16	1 19/32	1 5/16	9 1/2
856-080FT	8	13 9/16	6 1/4	1 11/16	1 15/32	11 3/4
856-100FT	10	16	7 13/32	1 7/8	1 9/16	14 3/8
856-120FT	12	19	9	1 15/16	1 21/32	17 1/32

FT Represents FiberTuff Ring.




Reducing TBE Nipple

Part No	Size (in)	L	N	H	Q
882-101	$\frac{3}{4} \times \frac{1}{2}$	1 1/2	1/8	25/32	1 1/8




WYE

Part No	Size (in)	L	J	H
875-020	2	3 19/32	5/8	3
875-030	3	5 23/32	1	6 21/32
875-040	4	6 9/16	1	5 3/4
875-060	6	9 1/2	1 13/32	8 1/16
875-080	8	13 9/32	2 1/32	11 1/4




Reducing WYE

Part No	Size (in)	L	J	H
876-420*	4 x 4 x 2	6 9/16	1	7 1/32
876-422*	4 x 4 x 3	6 9/16	1	6 1/2
876-528*	6 x 6 x 2	6 19/32	0	8 7/16
876-530*	6 x 6 x 3	6 19/32	0	7 27/32
876-532	6 x 6 x 4	6 19/32	0	7 1/8
876-578*	8 x 8 x 2	8	3/8	10 13/16
876-580*	8 x 8 x 3	8	3/8	10 1/4
876-582	8 x 8 x 4	8	3/8	9 1/2
876-585*	8 x 8 x 6	13 9/32	2 3/32	16 1/16




Union (O-Ring Type)

Part No	Size (in)	L	S	N	T
896-005	$\frac{1}{2}$	3 1/4	15/16	2 5/16	25/32
896-007	$\frac{3}{4}$	3 21/32	1 1/16	2 19/32	5/8
896-010	1	3 27/32	1 3/16	2 11/16	13/16
896-012	1 1/4	4 1/8	1 5/16	2 13/16	1 1/8
896-015	1 1/2	5 9/32	1 7/16	3 27/32	1
896-020	2	5 1/16	1 19/32	3 1/2	1 1/4
896-030	3	5 1/2	2	3 1/2	1 3/32
896-168	1 1/4 x 1	4 7/32	1 5/16	2 29/32	15/16




Union (O-Ring Type)

Part No	Size (in)	L	N	S
897-002	¼	1 5/8	3/8	5/8
897-003	⅜	1 15/16	13/32	25/32
897-005	½	2 5/32	5/16	15/16
897-007	¾	2 7/16	1/4	1 3/32
897-010	1	2 23/32	3/8	1 3/16
897-012	1¼	3	3/8	1 5/16
897-015	1½	3 1/4	3/8	1 7/16
897-020	2	3 9/16	7/16	1 19/32
897-030	3	4 7/16	15/32	2



Union (O-Ring Type)

Part No	Size (in)	L	N	T
898-005	½	1 15/16	1/2	23/32
898-007	¾	2	17/32	3/4
898-010	1	2 3/8	19/32	7/8
898-012	1¼	2 7/16	5/8	15/16
898-015	1½	2 17/32	11/16	15/16
898-020	2	2 29/32	15/16	1
898-030	3	4	1 1/8	1 7/16
898-040	4	4 11/16	1 5/8	1 17/32



Union (O-Ring Type)

Part No	Size (in)	L	N	S	T
899-005	½	2 5/32	17/32	15/16	23/32
899-007	¾	2 11/32	17/32	1 3/32	3/4
899-010	1	2 3/8	5/16	1 3/16	7/8
899-012	1¼	2 27/32	19/32	1 5/16	15/16
899-015	1½	3	11/16	1 7/16	29/32
899-020	2	3 15/32	27/32	1 19/32	1 1/32